

aTCA-80302PA

3U 2-slot Full-Mesh 40G AdvancedTCA® Shelf

Features

- 19" Rackmount, 3U height, 385mm depth
- 2-slot full-mesh topology Fabric Interface
- 2-slot standard Rear Transition Module
- Dual-bussed IPMB
- Hot-swappable IPMC controlled fan trays
- Two shelf management controller slots
- Dual 115 VAC/230 V AC power supply units





Specifications

Mechanical

19" Rackmount, 3U height, 385mm depth

Specification

Fits inside a 600 mm deep cabinet (include cable bend area) Supports 2-slot standard AdvancedTCA® blades and RTMs

Shelf Manager

Dual-hot-swappable Pigeon Point Systems ShMM-700 based ShMCs or Built-in simple Shelf manger function in intelligent fan trays Active/Standby mode for high availability applications Support multiple management functions:

- Monitoring temperature in the shelf and on the board
- Running cooling algorithm based on temperature conditions
- Hot-swapping blades (Activate and deactivate ATCA blade when receiving hot-swap messaging)
- Monitoring fan fault condition
- Indicating fan tray (separate left and right) fault and power supply fault at front panel $\,$

Cooling System

Hot-swappable IPMC controlled fan trays Easily removable replaceable air filter

Backplane

Hub-hub topology Base Interface Full-Mesh topology Fabric Interface Update channels for active/standby synchronization Dual-bussed IPMB

Power Input

90 VAC to 140 VAC / 170 VAC to 264 VAC Nominal 115VAC/230VAC Dual redundant AC power supply units Input nominal current 180V@7.9A (1200W) Weight: 18 kg

Operating Temp.

+5°C to +40°C (long term) -5°C to +55°C (short term)

Storage Temp.

-40°C to +70°C

Humidity

5% to 85%, non-condensing Dimensions: 483 x 132 x 385mm (W x H x D) Compliance: PICMG 3.0 Rev. 3.0 compatible Target Certifications: FCC, CE, UL

Ordering Information

Shelves

aTCA-80302PA/FM40AA2

3U 2-slot Rackmount AdvancedTCA® Shelf, Dual-Star Fabric Topology, Full-Mesh IPMI Bus 2 PPS ShMM-700 based ShMCs 2 power supply units

aTCA-80302PA/FM40S2

3U 2-slot Rackmount AdvancedTCA® Shelf, Dual-Star Fabric Topology, Full-Mesh IPMI Bus Built-in simple ShMC 2 power supply units

Power Supply (Optional)

aTCA-8AP/PSU1200
1200W VAC power supply unit

ShMC (Optional)

aTCA-8AP/ShMC700

Pigeon Point Systems ShMM-700 based ShMC

Dimensions



